

DL03-4 IP65 DOWNLIGHT

125mm



IP65

SPECIFICATIONS

Material Specifications

| | |
|--------------------------------|--|
| Material Specifications | Aluminium Diecast Housing / Clear Diffuser (Satin & Opal Lens Options Available) |
| Colour | White Trim (Custom Colour Options Available) |
| Cutout | 125mm |
| Dimensions | 144mm (Face Dia) x 71mm (H) |
| Ingress Protection | IP65 |
| Warranty | 5 Year Replacement |

Electrical Specifications

| | |
|-----------------------------------|------------------------|
| LED Wattage | 20W Max. |
| Power Supply | Tridonic TRIAC |
| Options | Tridonic DALI |
| Operating Temperature (Ta) | -20°C to +40°C |
| Connection Method | Australian Flex & Plug |

Optic Specifications

| | |
|--------------------------------------|---------------------------------------|
| Light Source | Philips COB |
| CRI | 90+ |
| Delivered Lumens | 640Lm - 1600Lm NFC Programmable |
| Beam Angle | 60° |
| Correlated Colour Temperature | 2700K / 3000K / 3500K / 4000K / 5000K |
| Rated Lifetime (L80B10) | >50,000hr |

VARIATIONS

| | |
|-------------------|----------------------------|
| DL03-4-27K | 8W - 20W Multi-Watt, 2700K |
| DL03-4-3K | 8W - 20W Multi-Watt, 3000K |
| DL03-4-35K | 8W - 20W Multi-Watt, 3500K |
| DL03-4-4K | 8W - 20W Multi-Watt, 4000K |
| DL03-4-5K | 8W - 20W Multi-Watt, 5000K |

