


# DL03-8 IP65 Downlight

## 200mm



### IP65

## SPECIFICATIONS

### Material Specifications

<b>Material Specifications</b>	Aluminium Die-cast Housing / Clear Diffuser (Satin & Opal Lens Options Available)
<b>Colour</b>	White Trim (Custom Colour Options Available)
<b>Dimensions</b>	226mm (Face Dia) x 96mm (H)
<b>Cutout</b>	200mm
<b>Ingress Protection</b>	IP65
<b>Warranty</b>	5 Year Replacement

### Electrical Specifications

<b>LED Wattage</b>	50W
<b>Power Supply</b>	Tridonic Fixed Output (NFC Programmable)
<b>Options</b>	Tridonic DALI
<b>Operating Temperature (Ta)</b>	-20°C to +40°C
<b>Connection Method</b>	Australian Flex & Plug

### Optic Specifications

<b>Light Source</b>	CITIZEN COB
<b>CRI</b>	90+
<b>Delivered Lumens</b>	680Lm - 4250Lm
<b>Beam Angle</b>	60°
<b>Correlated Colour Temperature</b>	2700K / 3000K / 3500K / 4000K / 5000K
<b>Rated Lifetime (L80B10)</b>	>50,000hr

## VARIATIONS

<b>DL03-8-27K</b>	8W - 50W Multi-Watt, 2700K
<b>DL03-8-3K</b>	8W - 50W Multi-Watt, 3000K
<b>DL03-8-35K</b>	8W - 50W Multi-Watt, 3500K
<b>DL03-8-4K</b>	8W - 50W Multi-Watt, 4000K
<b>DL03-8-5K</b>	8W - 50W Multi-Watt, 5000K

