

IP66 / IK10

Round Bunker

The Fortlite is an IP66 bunker ideal for commercial and residential applications.

It features Tri-Colour and Multi-Watt selectable technologies, giving installers a choice of 3 colour temperatures and 3 wattages within 1 fitting. Rated IK10, suitable for high vandalism areas, it has a die-cast aluminium enclosure that is corrosion and UV resistant.

Multiple cable entry points, a large 6mm terminal block facilitates quick and easy installation.



IP66



IPART VEET



SPECIFICATIONS

Material Specifications


Material	Die-cast Aluminium Housing with Opal PC Diffuser
Finish	Black
Dimensions	309mm Dia x 88mm (H)
Ingress Protection	IP66
Impact Rating	IK10
Weight	0.82Kg
Warranty	5 Year Replacement

Electrical Specifications

Input Voltage	Multi-Watt Selectable 22W / 15W / 10W
Accessories	283109 - Eyelid Cover
Accessories	283049 - Emergency Kit - D32 Classification
Accessories	283059 - Microwave Sensor Kit

Optic Specifications

Light Source	Tri-Colour Selectable 3K / 4K / 5K
Delivered Lumens	900Lm - 2000Lm
Beam Angle	110°
CRI	80Ra
Reported L70 (Hours)	> 50,000 Hrs



VARIATIONS

281005-10-3K	10W 900Lm 3000K
281005-15-3K	15W 1400Lm 3000K
281005-22-3K	22W 1850Lm 3000K
281005-10-4K	10W 1000Lm 4000K
281005-15-4K	15W 1500Lm 4000K
281005-22-4K	22W 2000Lm 4000K
281005-10-5K	10W 1000Lm 5000K
281005-15-5K	15W 1500Lm 5000K
281005-22-5K	22W 2000Lm 5000K