

TRIAC DIMMABLE CONSTANT VOLTAGE IP20



SPECIFICATIONS

Material Specifications

Material	Polycarbonate UL44-VO
Ingress Protection	IP20
Warranty	5 Year Replacement

Electrical Specifications

Input Type	180-240V, 50-60Hz
Connection Method	Australian F&P
Output Voltage	12V - 24V DC Constant Voltage
Dimming	Triac
Power Factor	>0.95 @ Full Load
Thermal Testing	Ta Rating -30°C to +40°C
Dimming	5% - 100% Dimming Range

VARIATIONS

DR-CV-12-12	12W, 12V - 94mm x 36mm x 17mm
DR-CV-12-24	12W, 24V - 94mm x 36mm x 17mm
DR-CV-20-12	20W, 12V - 94mm x 36mm x 17mm
DR-CV-20-24	20W, 24V - 94mm x 36mm x 17mm
DR-CV-30-12	30W, 12V - 107mm x 40mm x 22mm
DR-CV-30-24	30W, 24V - 107mm x 40mm x 22mm
DR-CV-40-12	40W, 12V - 132mm x 44mm x 28mm
DR-CV-40-24	40W, 24V - 132mm x 44mm x 28mm
DR-CV-60-12	60W, 12V - 132mm x 44mm x 28mm
DR-CV-60-24	60W, 24V - 132mm x 44mm x 28mm
DR-CV-80-12	80W, 12V -170mm x 50mm x 30mm
DR-CV-80-24	80W, 24V -170mm x 50mm x 30mm

