

# LENNOX 72W

## Asymmetric Floodlight

The LENNOX 72W Linear Lens IP66 Floodlight is the premium series floodlight for the professional market. Die-Cast Aluminium for enhanced Dissipation. IP66 Waterproof. Asymmetric Beam Angle, for 100% Forward Throw Light, with no back-light, reducing light pollution and glare. Enhanced corrosion resistance, using AkzoNobel Powder Coating.

Designing for Industrial Environments including Farms, Swimming Centres, Coastal areas.



### SPECIFICATIONS

#### Material Specifications

Housing	Die-Cast Aluminium Design
Finish	AkzoNobel Powder Coat
Dimensions	370 x 265 x 75mm
Impact Rating	IK08
Ingress Protection	IP66
Warranty	5 Year Replacement

#### Electrical Specifications

Power Supply	Integrated MeanWell, Non-Dim
Input Voltage	240V; 50/60Hz

#### Optic Specifications

Light Source	Lumileds Luxeon SMD 5050
Delivered Lumens	25,400lm
CRI	80Ra
Beam Angle	120°
Colour Deviation	SDCM ≤ 4
Reported L70 (Hours)	> 54,000 Hrs
Calculated L70 (Hours)	154,000 Hrs

### VARIATIONS

ND2522	LENNOX 72W Floodlight, Black, 90x40°, Non-Dim, 4000K
--------	--

