

Brick Tracklight

Medium



SPECIFICATIONS

Material Specifications

Material	Aluminium
Colour	White / Black
Dimensions	270mm (W) x 34mm (D) x 75mm (H)
Ingress Protection	IP20
Warranty	5 Year Replacement
LED Wattage	20W
Power Supply	TRIAC Dimmable
Options	DALI
Operating Temperature (Ta)	-20°C - +32°C
Connection Method	3~ Track Adaptor (1~ Available on request)

Optic Specifications

Light Source	Luminus SMD - SST20
CRI	95+
Beam Angle	15° / 30° / 45°
Correlated Colour Temperature	2700K / 3000K / 4000K
Rated Lifetime (L70B20)	>50,000hr

VARIATIONS

LX4T110-27-15-W	15°, 2700K, White, 1643Lm
LX4T110-30-15-W	15°, 3000K, White, 1777Lm
LX4T110-40-15-W	15°, 4000K, White, 2045Lm
LX4T110-27-30-W	30°, 2700K, White, 1643m
LX4T110-30-30-W	30°, 3000K, White, 1777Lm
LX4T110-40-30-W	30°, 4000K, White, 2045Lm
LX4T110-27-45-W	45°, 2700K, White, 1643Lm
LX4T110-30-45-W	45°, 3000K, White, 1777Lm
LX4T110-40-45-W	45°, 4000K, White, 2045Lm
LX4T110-27-15-B	15°, 2700K, Black, 1643Lm
LX4T110-30-15-B	15°, 3000K, Black, 1777Lm
LX4T110-40-15-B	15°, 4000K, Black, 2045Lm
LX4T110-27-30-B	30°, 2700K, Black, 1643Lm
LX4T110-30-30-B	30°, 3000K, Black, 1777Lm
LX4T110-40-30-B	30°, 4000K, Black, 2045Lm
LX4T110-27-45-B	45°, 2700K, Black, 1643Lm
LX4T110-30-45-B	45°, 3000K, Black, 1777Lm
LX4T110-40-45-B	45°, 4000K, Black, 2045Lm

